

Charging Station COOKIE STATION 22

Mode 3 electric charging system

The COOKIE STATION 22 charging station is the ideal system for public installations. Thanks to its features it connects to the BeaglePlug management platform. It is equipped as standard with devices for detecting the dispersions on the side of the car (mandatory by law), shutters and is already adequate in compliance with the MID standard. Available in models of 7.4 and 22 kW, it is ideal for any type of installation.

The COOKIE STATION 22 charging station has state-of-the-art technology to provide maximum charging performance.





MAIN FEATURES

- Always connected via LAN.
- Management by APP
- MID certificate
- Integrated protection against DC leakage.
- Body certified for installations in marine areas



GENERAL SPECIFICATIONS

- Connector type: 2 Type 2 sockets with Shutter
- Dimensions: 1400 x 320 x
 215 mm
- Weight 33 kg
- Material: Galvanized and painted steel
- Compatible with SDLM via SDLM Box



ELECTRICAL SPECIFICATIONS

- Maximum output: 7.4 kW (1P) /22kw (3P) for each connector
- Maximum current: 64 A
- Nominal frequency: 50/60 Hz
- Input voltage: 230/400 V AC 15%
- Configurable charging current from 6 to 32 A for each connector
- Protection IP54/IK10 (IK08 display)
- Residual current detection:
 DCLeakage 6mA (CC) + RCD
 TypeA 30 mA

BEAGLEPLUG® is a registered trademark of Eurolink Systems s.r.l.